

ORLIK[®] COMPRESSORS **original**

Piston compressors range 4 - 9



PKS 4 /40



EKN 9



PKS 9/100



SKS 9/100

Piston compressors ORLIK original are used in heavy duty industry

Piston compressors range 4 - 9

Main advantages of compressors ORLIK original:

- First-class quality warranted with the long tradition of the production of piston compressors
- Guarantee 6 years on the tank and 3 years on the compressor
- Nearly maintenance-free
- Easy compatibility of spare parts

■ Range 4

Type	Suction capacity (m ³ /h)	Capacity related to suction (m ³ /h)	Max. overpressure (bar)	Automatic cycle range (bar)	Electromotor Output (kW)	Electromotor Voltage (V)	Average noise level (dB)	Connection dimension	Weight (kg)	Pressure tank volume (l)	Dimensions L x W x H (mm)
EK 4	7,4	4,3	10	-	0,75	3 x 400	72	DN8	20,5	-	420 x 300 x 370
EKP 4*	7,4	4,3	10	-	0,75	3 x 400	72	DN8	21,5	-	420 x 300 x 400
EK 4 - 2	7,4	4,3	10	-	0,75	230	72	DN8	20	-	460 x 300 x 380
PKS 4 - 2/25	7,4	4,3	10	6,5 - 9	0,75	230	73	DN10	41	25	535 x 391 x 770
PKS 4/40	7,4	4,3	10	6,5 - 9	0,75	3 x 400	73	G1/4"	47	40	805 x 390 x 750
SKS 4/100	7,4	4,3	10	6,5 - 9	0,75	3 x 400	73	G3/8"	83	100	500 x 500 x 1025
SKS 4 - 2/100	7,4	4,3	10	6,5 - 9	0,75	230	73	G3/8"	81	100	500 x 500 x 1025

* EKP 4 is equipped with motor starter, which protects the electromotor from overloading, and with a 5 m supply cable with a fork. DN = connection for a hose

■ Range 9

Type	Suction capacity (m ³ /h)	Capacity related to suction (m ³ /h)	Max. overpressure (bar)	Automatic cycle range (bar)	Electromotor Output (kW)	Electromotor Voltage (V)	Average noise level (dB)	Connection dimension	Weight (kg)	Pressure tank volume (l)	Dimensions L x W x H (mm)
EK 9	15,1	9	10	-	1,5	3 x 400	75	M16x1,5	31	-	450 x 440 x 340
EKN 9	15,1	9	12	9 - 12	1,5	3 x 400	76	-	45	-	534 x 565 x 974
PKS 9/40	15,1	9	10	6,5 - 9	1,5	3 x 400	76	G1/4"	57	40	805 x 435 x 730
PKS 9/100	15,1	9	10	6,5 - 9	1,5	3 x 400	76	G1/4"	85	100	929 x 525 x 870
SKS 9/100	15,1	9	10	6,5 - 9	1,5	3 x 400	76	G3/8"	90	100	500 x 500 x 996
SKS 9/200	15,1	9	10	6,5 - 9	1,5	3 x 400	76	G3/8"	116	200	500 x 500 x 1524
SKS 9/200/12	15,1	9	12	9 - 12	1,5	3 x 400	76	G3/8"	129	200	500 x 500 x 1524

- Compressors without a pressure tank are designed for an environment with an ambient temperature of -5°C do +40°C.
- Compressors with a pressure tank are designed for an environment with an ambient temperature of +5°C do +40°C.

COMPRESSORS WITH A PRESSURE TANK, INCLUDING THE EKN 9 COMPRESSOR, OPERATE IN THE RANGE OF THE AUTOMATIC CYCLE ACCORDING TO THE TABLE.

Your distributor and professional adviser: